

Attorney Docket No.: 5762.200-US
Application Serial No.: 09/577,694
Filed: May 22, 2000
Inventors: Sorensen et al.
Via Facsimile: 571-273-8300

In the Claims

Please amend the claims as follows:

Claims (1-62) – Cancelled

63. (Currently Amended) A stopper comprising an injection-mouldable material, comprising: made of a blend of a butyl based rubber and a polyolefin, ~~wherein the polyolefin is not an elastomer, and~~ wherein the butyl based rubber is present in an amount of 70-90 % by weight and the polyolefin is present in an amount of 30-10 % by weight, and wherein the combination of the butyl based rubber and the polyolefin results in a reduced leakage of substances compared to the leakage of substances from a stopper made from a butyl based rubber alone and wherein the stopper injection-mouldable material, further comprises: 10 % by weight or less of fillers and 1% by weight or less of additives, provided that the injection-mouldable material comprises other than a thermoplastic elastomer.

64. (Previously Presented) The stopper according to claim 63 having a hardness of 40-80 Shore

65. (Previously Presented) The stopper according to the claim 63 having a hardness of 45-75 Shore A.

66. (Previously Presented).The stopper according claim 63 having a hardness of 65-75 Shore A.

67. (Previously Presented) The stopper according to claim 63 for a medical container, comprising a blend of 13-25 % by weight of a polyolefin and 75-87 % by weight of a butyl based rubber.

Attorney Docket No.: 5762.200-US
Application Serial No.: 09/577,694
Filed: May 22, 2000
Inventors: Sorensen et al.
Via Facsimile: 571-273-8300

68. (Previously Presented) The stopper according to claim 63, wherein the polyolefin is selected from the group of polyolefines consisting of polypropylene and polyethylene.
69. (Previously Presented New) The stopper claim 63, wherein the butyl based rubber is halogenated butyl.
70. (Previously Presented) The stopper claim 63, wherein the butyl based rubber is a bromobutyl.
71. (Previously Presented) The stopper according to claim 63, wherein the butyl based rubber is at least partially cross-linked.
72. (Previously Presented) The stopper according to claim 63 wherein the stopper has a substantially circular cross-section.
73. (Currently Amended) A medical container for storing a liquid medicament, comprising a distal and a proximal end portion and at least one wall defining an interior space for such liquid medicament, wherein one of the end portions comprises a stopper comprising: an injection-mouldable material, comprising: made of a blend of butyl based rubber and a polyolefin, ~~wherein the polyolefin is not an elastomer, and~~ wherein the butyl based rubber is present in an amount of 70-90 % by weight and the polyolefin is present in an amount of 30-10 % by weight, and wherein the combination of the butyl based rubber and the polyolefin results in a reduced leakage of substances compared to the leakage of substances from a stopper made from a butyl based rubber alone and wherein the ~~stopper~~ injection-mouldable material, further comprises: 10 % by weight or less of fillers and 1% by weight or less of

Attorney Docket No.: 5762.200-US
Application Serial No.: 09/577,694
Filed: May 22, 2000
Inventors: Sorensen et al.
Via Facsimile: 571-273-8300

additives, provided that the injection-mouldable material comprises other than a thermoplastic elastomer.

74. (Previously Presented) The medical container according to claim 72, wherein the at least one wall is non-flexible.

75. (Currently Amended) A process of producing a stopper as defined in claim 1, comprising the steps of:

- heating **materials consisting essentially of:** a butyl based rubber present in an amount of 70-90 % by weight, and melting a polyolefin present in an amount of 30-10 % by weight, ~~wherein the polyolefin is non-elastomeric, and~~ wherein fillers are added at less than 10% by weight and additives are added at less than 1%;
- homogenising the stopper material,
- moulding the stopper material by injection moulding and
- obtaining the stopper.

76. (Previously Presented) A process of producing a stopper according to claim 74, wherein the stopper is moulded on to a rod by the means of two-component injection moulding.

77. (Currently Amended) A stopper comprising an injection-mouldable material, **consisting essentially of: made of a blend of a** butyl based rubber and a polyolefin, ~~wherein the polyolefin is not an elastomer, and~~ wherein the butyl based rubber is present in an amount of 70-90 % by weight and wherein additives are optionally present in an amount not exceeding 1% by weight and fillers are optionally present in an amount less than 10% by weight and wherein the balance of the material is polyolefin, and wherein the combination of

Attorney Docket No.: 5762.200-US
Application Serial No.: 09/577,694
Filed: May 22, 2000
Inventors: Sorensen et al.
Via Facsimile: 571-273-8300

the butyl based rubber and the polyolefin results in a reduced leakage of substances compared to the leakage of substances from a stopper made from a butyl based rubber alone.

78. (Previously Presented) The stopper according to claim 77 having a hardness of 40-80 Shore A.

79. (Previously Presented) The stopper according to the claim 77 having a hardness of 65-75 Shore A.

80. (Currently Amended) The stopper according to claim 77 for a medical container, wherein the injection-mouldable material, consists essentially of: comprising a blend of 13-25 % by weight of a polyolefin and 75-87 % by weight of a butyl based rubber.

81. (Previously Presented) The stopper according to claim 77, wherein the polyolefin is selected from the group of polyolefines consisting of polypropylene and polyethylene.

82. (Previously Presented) The stopper claim 77, wherein the butyl based rubber is halogenated butyl.

83. (Previously Presented) The stopper claim 77, wherein the butyl based rubber is a bromobutyl.

84. (Previously Presented) The stopper according to claim 77, wherein the butyl based rubber is at least partially cross-linked.

Attorney Docket No.: 5762.200-US
Application Serial No.: 09/577,694
Filed: May 22, 2000
Inventors: Sorensen et al.
Via Facsimile: 571-273-8300

85. (Previously Presented) The stopper according to claim 77 wherein the stopper has a substantially circular cross-section.